
HG Installation Instructions



This Neon Transformer is Dry Type 7 and is suitable for use only in dry locations.

Connect the transformer cord and plug set to a three-wire socket that contains a line, neutral, and grounding conductor. The connection between the transformer secondary GTO cable and the neon tubing is to be insulated for the secondary output voltage involved. Encase the transformer secondary GTO cable in approved sleeving. Affix the sleeving to the transformer using the GTO exit collars provided. Mechanically secure the transformer using the hanger brackets and appropriate hardware for the transformer weight and building materials.

	etzer company	LU	LUMINOUS TUBE FOOTAGE CHART															
TRANSFORMER RATING		Approximate Number of Feet of Tubing Operated 1																
Secondary Voltage V	Short-Circuit Current mA	Clear or Fluorescent Red Neon (Also Recommended for Neon Fluorescent Gold Tube Size, Millimeters Clear or Fluorescent Mercury Filled Tubes All Colors (All Enclosed Applications) ² Tube Size, Millimeters													Secondary Voltage V			
		18	15	14	13	12	11	10	9	18	15	14	13	12	11	10	9	
15,000	30 / 60	72	60	54	50	45	40	36	32	80	72	64	60	54	48	44	39	15,000
12,000	30 / 60	55	45	42	39	35	32	29	26	62	55	50	46	42	38	35	31	12,000
10,500	30 / 60	48	39	36	34	31	28	25	22	54	48	43	40	37	33	30	27	10,500
9,000	30/ 60	40	33	30	29	26	24	21	18	45	40	36	33	31	26	25	22	9,000
7,500	30/ 60	28	26	24	22	21	19	17	15	35	31	28	27	25	23	20	18	7,500
6,000	30/ 60	23	20	19	18	16	15	13	12	26	24	23	21	19	18	16	14	6,000
5,000	30/ 60	19	17	16	15	12	11	10	8	23	20	19	16	15	13	12	10	5,000
4,000	30/ 60	16	13	12	11	10	9	8	7	19	16	14	13	12	10	9	8	4,000
3,000	30/ 60	11	10	9	9	8	7	6	5	14	12	11	10	9	8	7	6	3,000
Recommended Gas		8	9	10	10	11	12	13	15	8	9	10	10	11	12	13	15	

(1) Based on average grade. (2) All enclosed applications. Exposed and extremely cold climates may require footage be reduced by 10-20%. NOTE 1: Deduct approximately 1 foot from above figures for each pair of electrodes.

NOTE 2: Recommended gas pressure for 10-ft plus lengths. Increase 10% for tube lengths under 10 ft.

EDANCE

2268 Fairview Boulevard • Fairview, Tennessee 37062 • http://www.franceformer.com