

# Glass Housings



#100 Housing



#200 Housing



#200P Housing



#300 Housing



#300P Housing

- ◆ Affordable and safe method for making neon electrode connections in raceways
- ◆ Borosilicate heat resistant glass
- ◆ Spring contact allows for easy neon tube servicing
- ◆ Rated for 7500 volt applications, including 15000 V mid-point referenced transformer installations
- ◆ Comes with a plated steel ferrule to secure the unit to the sign enclosure
- ◆ #300 and #300P recommended for use with new UL2161 Listed transformers to minimize nuisance tripping



Description	Part Number	Catalog Number	Panel Hole	Housing Opening	Overall Height	Packaging	Weight
#100 Glass Housing	38282	GH100	1 3/4"	1 1/4"	3 5/8"	100 per box	31 lbs
#200 Glass Housing	38283	GH200	1 3/8"	7/8"	3 1/2"	100 per box	20 lbs
#200P Glass Housing	38284	GH200P	1 3/8"	7/8"	2 1/2"	100 per box	16 lbs
#300 Glass Housing	38285	GH300	1 1/2"	1 1/8"	3 1/2"	100 per box	20 lbs
#300P Glass Housing	38286	GH300P	1 1/2"	1 1/8"	3 1/2"	100 per box	20 lbs

[www.sfeg.com/france](http://www.sfeg.com/france)